

Claims:

1. A bed comprising:
a posterior bed support including a base, a posterior body portion
coupled to the base, and a posterior support plate configured to be removably coupled
5 to the posterior body portion and supported for sliding movement into the posterior
body portion; and
an anterior bed support coupled to the posterior bed support, the
anterior bed support including an anterior body portion, an anterior support plate
configured to be removably coupled to the anterior body portion and supported for
10 sliding movement into the anterior body portion, and a proning support surface
coupled to the anterior support plate.
2. The bed of claim 1, further comprising a mover configured to rotate
the proning support surface about a longitudinal axis.
3. The bed of claim 1, further comprising a patient support surface
15 configured to be removably coupled to the posterior support plate.
4. The bed of claim 1, wherein the posterior body portion includes a
plurality of fluid passageways, and the posterior support plate includes a plurality of
fluid passageways configured to communicate with the fluid passageways of the
posterior body portion when the posterior support plate is coupled to the posterior
20 body portion.
5. The bed of claim 4, further comprising a fluid supply coupled to the
plurality of fluid passageways of the posterior body portion.
6. The bed of claim 1, wherein the posterior body portion includes
spaced-apart inner side walls and side notches extending into the inner side walls, and
25 the posterior support plate includes a central portion and spaced-apart outer lips
coupled to the central portion, the outer lips of the posterior support plate being
configured to slide through the notches of the posterior body portion.
7. The bed of claim 6, wherein the anterior body portion includes spaced-
apart inner side walls and side notches extending into the inner side walls, and the
anterior support plate includes a central portion and spaced-apart outer lips coupled to
30 the central portion, the outer lips of the anterior support plate being configured to
slide through the notches of the anterior body portion.

8. A bed comprising:

a bed support including a base, a body portion coupled to the base, and a support plate configured to be removably coupled to the body portion, the body portion including a guide configured to operably couple with the support plate in order to guide the support plate in sliding movement into the body portion; and
5 a patient support surface configured to be releasably coupled to the support plate.

9. The bed of claim 8, wherein body portion includes spaced-apart inner side walls, the guide includes side notches extending into the inner side walls, and the
10 support plate includes a central portion and spaced-apart outer lips coupled to the central portion, the outer lips of the support plate being configured to slide through the notches of the body portion.

10. The bed of claim 8, wherein the body portion includes a plurality of fluid passageways, and the support plate includes a plurality of fluid passageways
15 configured to communicate with the fluid passageways of the body portion when the support plate is coupled to the body portion.

11. The bed of claim 10, wherein the plurality of fluid passageways of the body portion and the plurality of passageways of the support plate when in fluid communication define a plurality of pathways, the pathways configured to be
20 uninterrupted when the support plate is coupled to the body portion and is slidably moved relative to the body portion.

12. The bed of claim 11, further comprising flexible hoses which couple the passageways of the body portion to the passageways of the support plate.

13. The bed of claim 10, further comprising a fluid supply coupled to the
25 fluid passageways of the body portion.

14. The bed of claim 8, wherein the support plate is configured to slidably move relative to the base portion when coupled to the base portion in order to position a patient supported on the patient support surface.

15. The bed of claim 8, further comprising a mover configured to rotate
30 the patient support surface about a longitudinal axis.

16. A bed comprising:
a posterior bed support; and

an anterior bed support coupled to the posterior bed support, the anterior bed support including an anterior body portion, an anterior support plate configured to be removably coupled to the anterior body portion and supported for sliding movement into the anterior body portion, and a proning support surface coupled to the anterior support plate, the anterior body portion including a guide configured to operably couple with the anterior support plate in order to guide the anterior support plate in sliding movement.

17. The bed of claim 16, wherein anterior body portion includes spaced-apart inner side walls, the guide includes side notches extending into the inner side walls, and the anterior support plate includes a central portion and spaced-apart outer lips coupled to the central portion, the outer lips of the anterior support plate being configured to slide through the notches of the anterior body portion.

18. The bed of claim 16, wherein the anterior body portion includes a passageway, the anterior support plate includes a passageway, and the proning support surface includes a passageway, the passageways of the anterior body portion, the anterior support plate, and the proning support surface cooperating to define a fluid pathway when the anterior body portion and the proning support surface are coupled to the anterior support plate.

19. The bed of claim 16, further comprising a mover configured to rotate the proning support surface about a longitudinal axis.

20. The bed of claim 16, wherein the proning support surface includes a mattress and a proning platform coupled to the mattress.